

# PULL PLOW Two plows are better than one!





www.danielsplows.com

## **Incredibly Efficient**

- The Daniels Pull Plow doesn't replace your front-mounted plow - it complements it by cleanly removing snow and ice from those hard-to-plow areas that your front mounted plow simply isn't designed to efficiently handle.
- Thanks to 2,000 lbs of down pressure; driveways, loading docks and circle drives are cleared in record time - right down to the pavement!
- Unlike the competitor back blades, the Daniels Pull Plow requires absolutely no modifications to your vehicle in order to install
- Since your snow removal actions are always done while moving forward, it's much safer than backdragging snow into a crowded, busy street!
- The Daniels Pull Plow fits virtually any 4WD vehicle equipped with a 2" receivertype hitch. Thanks to the patented SPEEDHITCH<sup>™</sup> — hook-up is fast and easy!
  - Simply connect the SPEEDHITCH™ to the vehicle's standard 2" receiver-type hitch and connect chain to the truck frame.
  - Connect the drawbar arms to the "ears" on the T-bar, then connect the horizontal arm.
  - 3 The entire plow assembly can be removed from the vehicle in under 30 seconds, freeing the rear of the truck for other uses.



Model Number	6202	7202	8002	9002	9602	10202
Plow Width	62" (5'-2")	72" (6')	80" (6'-8")	90" (7'-6")	96" (8')	102" (8'-6")
Overall Dimensions						
Weight (lbs.)	250	275	300	325	350	375
Height	19"	19"	19"	19"	19"	19"
Material Specifications						
Moldboard	8 gauge	8 gauge	8 gauge	8 gauge	8 gauge	8 gauge
Side Plates	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Draw bar arms	1" x 2"	1" x 2"	1" x 2"	1" x 2"	1" x 2"	1" x 2"
Cutting Edge – AR400 OR Poly Version Available	3/8" x 5"	3/8" x 5"	3/8" x 5"	3/8" x 5"	3/8" x 5"	3/8" x 5"

#### **SPECIAL FEATURES**

Clean, contained, out of the way, and accessible for maintenance. Easily installed and removed with the lift assembly. Does not affect the fast and easy 1,2,3 hook up.

Our all steel construction containment box houses all hydraulic and electrical components powering the plow.

Can be easily moved from one vehicle to another

Cycle time: 2.5 seconds

Daniels new low profile design allows full tailgate use



#### NO WELDING REQUIRED

#### **CLEARANCES: ALL MODELS**

Rear of bumper to end of plow: 26" Maximum lift height-side plates: 12" Maximum lift height-rear of plow: 18"

#### **RECOMMENDED APPLICATION**

- 62" UTVs
- 72" Toolcat, Kubota RTV
- 80" Jeep and small chassis trucks
- 90" 1/2 ton and full-size SUV
- 96" 3/4 and 1 ton trucks
- 102" Dually Truck



### 844-BLU-PLOW • www.danielsplows.com

